



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 1-3004: 4 Ply White Nitrile/OHGR

**Color:** White

**Plies:** 4

**Nom. OAG:** 0.158" +/- 0.02"

**Fabric:** Cotton/Polyester

**Top Surface:** 3/64" Smooth Cover

**Bottom Surface:** Friction Surface

**Compound:** NBR

**Work Tension:** 140 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.085 lbs./PIW

**Minimum Pulley:** 3"

**Backflex Min. Pulley Dia.:** 4.5"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 72"

**Attributes:** FDA Compliant, Oil Resistant,  
Sliderbed Suitable

**Top Cover Coefficient of Friction:** 1.4

**Bottom Cover Coefficient of Friction:**  
0.3

**Features:** 1-3004 features a special fabric treatment to insure the highest ply adhesion and the lowest moisture absorption. Refer to the Chemical Resistance Chart when choosing a cleaning solution. 4 Ply Nitrile can be used in any heavy duty food application. This belt has low moisture absorption and high resistance to oil and grease. This belt is very popular in the meat and fish industry.

