



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 1-3007: 3 Ply White FS x FS

**Color:** White

**Plies:** 3

**Nom. OAG:** 0.09" +/- 0.01"

**Fabric:** Cotton/Polyester

**Top Surface:** Friction Surface

**Bottom Surface:** Friction Surface

**Compound:** NBR

**Work Tension:** 48 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.055 lbs./PIW

**Minimum Pulley:** 3"

**Backflex Min. Pulley Dia.:** 4.5"

**Working Temp:** 0 to 250 °F

**Max. Stocked Width:** 72"

**Attributes:** FDA Compliant, Oil Resistant

**Top Cover CoF:** 0.3

**Bottom Cover CoF:** 0.3

### Features

1-3007 uses three plies of cotton-polyester fabric for flexibility, easy cleaning, and consistent performance in bakery environments. The smooth FS/FS construction supports quick sanitation and predictable product release.

The belt tracks well on sheeters, resists glazing, and maintains its shape under repetitive cycles.

3 Ply White FS x FS is widely used on dough sheeters and general bakery lines where a dependable, long-service general-purpose belt is required.

