



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 1-4003: 3 Ply Tylerwire

**Color:** White

**Plies:** 3

**Nom. OAG:** 0.155" +/- 0.015"

**Fabric:** Polyester

**Top Surface:** Tylerwire Impression

**Bottom Surface:** Friction Surface

**Compound:** NBR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.074 lbs./PIW

**Minimum Pulley:** 2.5"

**Backflex Min. Pulley Dia.:** 3.75"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 72"

**Attributes:** FDA Compliant, Oil Resistant,  
Sliderbed Suitable

**Top Cover Coefficient of Friction:** 1.3

**Bottom Cover Coefficient of Friction:**  
0.3

**Features:** This belt features a molded top surface that is excellent for moderate inclines and dough forming. The belt is easy to clean, flexible and non-marking. Refer to the chemical resistance chart when choosing a cleaning solution. 3 Ply Tylerwire is used for dough forming, inclines, pulley lagging and in the laundry industry.

