



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 1-5003: 3 Ply Teflon

**Color:** White

**Plies:** 3

**Nom. OAG:** 0.08" +/- 0.015"

**Fabric:** Polyester

**Top Surface:** .002 Thick Teflon

**Bottom Surface:** Friction Surface

**Compound:** PTFE (Teflon)

**Work Tension:** 100 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.043 lbs./PIW

**Minimum Pulley:** 2"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 60"

**Attributes:** FDA Compliant, Sliderbed Suitable

**Top Cover Coefficient of Friction:** 0.25

**Bottom Cover Coefficient of Friction:** 0.3

**Features:** This belt features a .002" thick teflon cover that is bonded to a high strength polyester carcass. The belt offers superb release qualities demanded by applications where hot or stick materials are encountered. Refer to the chemical resistance chart when choosing a cleaning solution. This belt is not recommended for troughing or back bend applications. 3 Ply Teflon is popular in confectionary, bakery and other food processing applications.

