



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 1-6003: 3 Ply Neoprene FS x FS

**Color:** Brown

**Plies:** 3

**Nom. OAG:** 0.066" +/- 0.01"

**Fabric:** Cotton/Polyester

**Top Surface:** Friction Surface

**Bottom Surface:** Friction Surface

**Compound:** NBR

**Work Tension:** 33 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.037 lbs./PIW

**Minimum Pulley:** 1"

**Backflex Min. Pulley Dia.:** 1.5"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 72"

**Attributes:** Non-Marking

**Top Cover Coefficient of Friction:** 0.5

**Bottom Cover Coefficient of Friction:**  
0.5

**Features:** 3 Ply Neoprene FS x FS features tightly woven fabric for general conveying. The belt is non-marking, very flexible, oil resistant and easy to clean. This belt can be made endless with cold vulcanizing cement as well as hot vulcanizing. Used to convey light duty products in most general industrial applications. Very popular in the printing industry.

