



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

2-1150: B1500 FBS

Color: Black

Plies: 1

Nom. OAG: 0.13" +/- 0.02"

Fabric: Interwoven Polyester

Top Surface: Friction Surface

Bottom Surface: Friction Surface

Compound: PVC

Work Tension: 150 lbs./PIW

Elongation: Less than 3%

Weight: 0.06 lbs./PIW

Minimum Pulley: 3"

Backflex Min. Pulley Dia.: 4.5"

Working Temp. (F): 0 to 180

Max. Stocked Width: 72"

Attributes: Fire Retardant, Sliderbed
Suitable

Top Cover Coefficient of Friction: 0.25

Bottom Cover Coefficient of Friction:
0.23

Features: This belt features the popular interwoven carcass. It offers high strength, tear resistance and low stretch. B1500 FBS is a medium duty general purpose conveyor belt that can be used in most industries.






Splicing Instructions

Part Number: 2-1150

Part Description: B1500 FBS



Finger Length (A):

Finger Width (B):

Imperial	Metric
3"	76 mm
3/4"	19 mm

Water Cooled

Hi-Speed

Upper Platen Temp:

Bottom Platen Temp:

Pressure:

Time:

	Imperial	Metric	Imperial	Metric
Upper Platen Temp:	340 ° F	171 ° C	340 ° F	171 ° C
Bottom Platen Temp:	340 ° F	171 ° C	340 ° F	171 ° C
Pressure:	50 PSI	3.4 bar	36 PSI	2.5 bar
Time:	01:00 m:s	01:00 m:s	03:00 m:s	03:00 m:s

Press Layout

Description

Part # to Order

	Top Heating Platen with equalizing plate	
	Teflon	6-3000
	Meltable Foil (optional)	8341C
	Belt	2-1150
	Teflon	6-3000
	Bottom Heating Platen with equalizing plate	

For high stress applications splice with reinforcing fabric.