



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 2-1201: B2000 COS

**Color:** Black

**Plies:** 1

**Nom. OAG:** 0.205" +/- 0.02"

**Fabric:** Interwoven Polyester

**Top Surface:** Smooth Cover

**Bottom Surface:** Brushed

**Compound:** PVC

**Work Tension:** 200 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.125 lbs./PIW

**Minimum Pulley:** 4"

**Backflex Min. Pulley Dia.:** 6"

**Working Temp. (F):** 0 to 180


**Max. Stocked Width:** 72"

**Attributes:** Sliderbed Suitable

**Top Cover Coefficient of Friction:** 0.8

**Bottom Cover Coefficient of Friction:**  
0.4

**Features:** 2-1201 features the popular interwoven carcass as well as a smooth PVC Top Cover. The bottom surface is brushed clean for a lower coefficient of friction. B2000 COS is a heavy duty general purpose conveyor belt that can be used in most industries. It offers high strength, tear resistance and low stretch.





# Splicing Instructions

**Part Number:** 2-1201

**Part Description:** B2000 COS



**Finger Length (A):**

**Finger Width (B):**

Imperial	Metric
3"	76 mm
3/4"	19 mm

## Water Cooled

## Hi-Speed

**Upper Platen Temp:**

**Bottom Platen Temp:**

**Pressure:**

**Time:**

	Imperial	Metric	Imperial	Metric
Upper Platen Temp:	340 ° F	171 ° C	340 ° F	171 ° C
Bottom Platen Temp:	340 ° F	171 ° C	340 ° F	171 ° C
Pressure:	50 PSI	3.4 bar	36 PSI	2.5 bar
Time:	01:00 m:s	01:00 m:s	03:00 m:s	03:00 m:s

## Press Layout

## Description

## Part # to Order

	Top Heating Platen with equalizing plate	
	Teflon	6-3000
	Meltable Foil (optional)	8341C
	Belt	2-1201
	Teflon	6-3000
	Bottom Heating Platen with equalizing plate	

For high stress applications splice with reinforcing fabric.