



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 2-1352: B3500 CBS

**Color:** Black

**Plies:** 1

**Nom. OAG:** 0.31" +/- 0.03"

**Fabric:** Interwoven Polyester

**Top Surface:** Smooth Cover

**Bottom Surface:** Smooth Cover

**Compound:** PVC

**Work Tension:** 350 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.165 lbs./PIW

**Minimum Pulley:** 8"

**Backflex Min. Pulley Dia.:** 12"

**Working Temp. (F):** 0 to 180

**Max. Stocked Width:** 48"

**Attributes:** Static Conductive to  $< 3 \times 10^8$  ohms, OSHA 29 CFR, Fire Retardant

**Features:** 2-1352 features an fire retardant, static conductive, oil resistant PVC. The tightly woven carcass resists fraying, has low stretch and has good lace retention. Do not use this belt on a slider bed application. B3500 CBS is a popular heavy duty bucket elevator belt and a heavy duty live roller belt. The thick carcass has good bolt retention. It is static conductive to less than 300 megohms per the OSHA requirement for bucket elevator conveyor belts.

