



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 3-1102: 2 Ply Black R/T

**Color:** Black

**Plies:** 2

**Nom. OAG:** 0.25" +/- 0.02"

**Recessed OAG:** 0.11"

**Fabric:** Polyester

**Top Surface:** Rubber Hemp Impression

**Bottom Surface:** Bare

**Compound:** SBR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.11 lbs./PIW

**Minimum Pulley:** 2"

**Backflex Min. Pulley Dia.:** 3"

**Working Temp. (F):** -20 to 250

**Max. Stocked Width:** 72"

**Attributes:** Troughable, Sliderbed  
Suitable

**Top Cover Coefficient of Friction:** 1.6

**Bottom Cover Coefficient of Friction:**  
0.4

**Features:** This belt offers excellent gripping for standard incline conveyors. The polyester carcass offers high strength and low stretch. NOTE--The rough top impression must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. 2 Ply Black rough top is the most popular incline belt in our product line. It will handle almost all products including boxed, bagged or packaged goods.

