



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 3-1203: 3 Ply Neoprene R/T

**Color:** Brown

**Plies:** 3

**Nom. OAG:** 0.255" +/- 0.02"

**Recessed OAG:** 0.11"

**Fabric:** Polyester

**Top Surface:** Hemp Impression Rough  
Top

**Bottom Surface:** Bare

**Compound:** NBR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.11 lbs./PIW

**Minimum Pulley:** 3"

**Backflex Min. Pulley Dia.:** 4.5"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 72"

**Attributes:** Troughable, Sliderbed  
Suitable

**Top Cover Coefficient of Friction:** 0.7

**Bottom Cover Coefficient of Friction:**  
0.3

**Features:** 3-1203 offers excellent gripping for standard incline conveyors. The NBR compound is oil resistant and non-marking. NOTE--The Rough Top impression must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. 3 Ply Neoprene Rough Top is popular in any area where a non-marking oil resistant rough top is needed. It is popular in the corrugated box industry as well as bakeries.

