



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 3-1600: P2GY Mono-Grip-S 8M/7P/ZP

**Color:** Gray

**Plies:** 2

**Nom. OAG:** 0.145" +/- 0.03"

**Fabric:** Monofilament

**Top Surface:** Low Durometer PVC

**Bottom Surface:** Bare

**Compound:** PVC

**Work Tension:** 100 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.072 lbs./PIW

**Minimum Pulley:** 2"

**Backflex Min. Pulley Dia.:** 3"

**Working Temp. (F):** 20 to 180

**Max. Stocked Width:** 78.75"

**Attributes:** Cross Rigid, Powerturn  
Suitable, Non-Marking, Sliderbed Suitable

**Features:** 3-1600 features a low durometer PVC top cover on a 2 ply monofilament carcass. This belt will provide a positive (sticky) carrying surface. The carcass will permit this belt to travel at high speeds with low noise. It is also known as a 'Sticky Top' belt. P2GY Mono-Grip-S 8M/7P/ZP can be used in package handling, manufacturing, post office applications. It is a high traction belt for moderate inclines.

