



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

3-4402: 2 Ply Tan Diamond Top

Color: Tan

Plies: 2

Nom. OAG: 0.313" +/- 0.02"

Recessed OAG: 0.15"

Fabric: Polyester

Top Surface: Diamond Top Impression

Bottom Surface: Bare

Compound: SBR

Work Tension: 150 lbs./PIW

Elongation: Less than 2%

Weight: 0.093 lbs./PIW

Minimum Pulley: 2.5"

Backflex Min. Pulley Dia.: 3.75"

Working Temp: -25 to 250 °F

Max. Stocked Width: 72"

Attributes: Sliderbed Suitable, Non-Marking

Hardness: 45a

Top Cover Coefficient of Friction: 1.9

Bottom Cover Coefficient of Friction: 0.3

Features:

3-4402 is designed for the steepest incline applications, providing exceptional traction where maximum performance and product control are required. The tan diamond-patterned top cover delivers an unusually high coefficient of friction, ensuring that boxed, bagged, and packaged items remain stable even on aggressive angles.

The 2-ply construction offers a balance of strength, flexibility, and durability, making this belt suitable for continuous-duty operations across a wide range of industries. The tan compound is also non-marking, an important benefit for facilities where product appearance or cleanliness is critical.

This belt is widely used in airline baggage handling, parcel distribution centers, and postal operations, where consistent grip and reliable incline performance are essential for throughput and efficiency.

(Note: The diamond/rough-top impression must be recessed to use mechanical lacing. Use Recessed OAG for proper installation and splice performance.)

