



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 4-4680: R900 Red Urethane

**Color:** Red

**Plies:** 1

**Nom. OAG:** 0.125" +/- 0.02"

**Fabric:** Interwoven Polyester

**Top Surface:** Smooth Cover

**Bottom Surface:** Friction Surface

**Compound:** Poly Urethane

**Work Tension:** 90 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.079 lbs./PIW

**Minimum Pulley:** 2"

**Backflex Min. Pulley Dia.:** 3"

**Working Temp. (F):** 0 to 185

**Max. Stocked Width:** 72"

**Attributes:** Sliderbed Suitable, Abrasion Resistant

**Hardness:** 85a

**Top Cover Coefficient of Friction:** 0.85

**Bottom Cover Coefficient of Friction:** 0.25

**Features:** This is one of the toughest, most abrasive resistant belts available. The 85 Durometer urethane cover will resist cutting and abrasion from metal, glass, aluminum and other abrasive materials. R900 Red Urethane is used in Metal Stamping, Recycling, Die Cutting and Brick Manufacturing applications.

