



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 4-4700: R1200 Red Urethane

**Color:** Red

**Plies:** 1

**Nom. OAG:** 0.187" +/- 0.02"

**Fabric:** Interwoven Polyester

**Top Surface:** Urethane

**Bottom Surface:** Friction Surface

**Compound:** Poly Urethane

**Work Tension:** 120 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.1 lbs./PIW

**Minimum Pulley:** 4"

**Backflex Min. Pulley Dia.:** 6"

**Working Temp. (F):** 0 to 185

**Max. Stocked Width:** 72"

**Attributes:** Sliderbed Suitable, Abrasion Resistant

**Hardness:** 85a

**Top Cover Coefficient of Friction:** 0.85

**Bottom Cover Coefficient of Friction:** 0.25

**Features:** This is one of the toughest, most abrasive belts on the market. The 3/32" thick, 85 Durometer urethane cover will resist cutting and abrasion from metal, glass, aluminum and other abrasive materials. R1200 Urethane-Novex is used in metal stamping, recycling, die cutting and brick manufacturing applications.

