



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 5-2335: 2 Ply 220 1/16 x 1/16 M-MOR-SC

**Color:** Black

**Plies:** 2

**Nom. OAG:** 0.215" +/- 0.03"

**Fabric:** Polyester/Nylon

**Top Surface:** Smooth Cover

**Top Cover Thickness:** 0.0625"

**Bottom Surface:** Smooth Cover

**Bottom Cover Thickness:** 0.0625"

**Compound:** SCORF

**Work Tension:** 220 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.136 lbs./PIW

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 72"

**Attributes:** Fire Retardant, Static  
Conductive to  $< 3 \times 10^8$  ohms, OSHA 29  
CFR, Oil Resistant, Troughable

**Hardness:** 65a

**Minimum Pulley Chart:**

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

**Features:** 5-2335 is static conductive, moderately oil resistant, fire retardant and MSHA approved for grain elevators. This belt is not approved for use in underground applications. 220 1/16 X 1/16 M-MOR-SC is an excellent belt for bucket elevator applications. Mulhern Belting can punch a wide variety of patterns for any bucket configuration in this belt. It is also ideal to convey oily grains or wood chips.

