



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-2442: 4 Ply 220 1/8 x 1/16 CR-MOR

Color: Black

Plies: 4

Nom. OAG: 0.46" +/- 0.03"

Fabric: Polyester/Monofilament

Top Surface: Smooth Cover

Top Cover Thickness: 0.125"

Bottom Surface: Smooth Cover

Bottom Cover Thickness: 0.0625"

Compound: MOR

Work Tension: 220 lbs./PIW

Elongation: Less than 4%

Weight: 0.23 lbs./PIW

Working Temp. (F): -20 to 225

Max. Stocked Width: 60"

Attributes: Cross Rigid, Oil Resistant

Hardness: 65a

Minimum Pulley Chart:

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

Features: 5-2442 features the same benefits as the 220 1/8" x 1/16" MOR with additional cross rigidity due to 2 additional monofilament plies. This belt is primarily used for sidewall fabrication. Do not use this belt in a troughing application. 220 1/8" x 1/16" CR-MOR is popular as the base belt in sidewall application due to its cross rigidity.

