



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 5-2731: 2 Ply 220 3/16 x 1/16 STD

**Color:** Black

**Plies:** 2

**Nom. OAG:** 0.36" +/- 0.03"

**Fabric:** Polyester/Nylon

**Top Surface:** Smooth Cover

**Bottom Surface:** Smooth Cover

**Compound:** SBR

**Work Tension:** 220 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.2 lbs./PIW

**Minimum Pulley:** 10"

**Working Temp:** -20 to 250 °F

**Max. Stocked Width:** 96"

**Attributes:** Troughable

**Hardness:** 65a

**Top Cover Thickness:** 0.188"

**Bottom Cover Thickness:** 0.063"

### Features

5-2731 features a smooth top and bottom surface. The heavy cover combined with a high-strength synthetic carcass provides a long-wearing, mildew-resistant, rot-resistant, low-stretch belt designed for demanding conditions.

220 3/16" x 1/16" STD is excellent for high-abrasion applications and is widely used in the sand, gravel, and rock industries, as well as other heavy industrial environments.

