



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-2734-SOR: 220 3/16 x 1/16 Hot Asphalt SOR

Color: Black

Plies: 2

Nom. OAG: 0.36" +/- 0.03"

Fabric: Polyester/Nylon

Top Surface: Smooth Cover

Top Cover Thickness: 0.1875"

Bottom Surface: Smooth Cover

Bottom Cover Thickness: 0.0625"

Compound: SOR

Work Tension: 220 lbs./PIW

Elongation: Less than 4%

Weight: 0.2 lbs./PIW

Working Temp. (F): -20 to 350

Max. Stocked Width: 72"

Attributes: Oil Resistance ASTM D471
70C/72hrs/IRM903 < 10% Swell,
Troughable, Oil Resistant

Hardness: 65a

Minimum Pulley Chart:

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

Features: 5-2734-SOR features a compound designed to service a combination of high temperature and oil. It has good abrasion resistance and retains flexibility in environments up to 350F in many applications. 220 3/16 x 1/16 SOR is popular carrying hot asphalt, oily grains and oil treated coal. It is also used in sewage treatment where oil can be a problem.

