



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 5-3731: 3 Ply 330 3/16 x 1/16 STD

**Color:** Black

**Plies:** 3

**Nom. OAG:** 0.41" +/- 0.03"

**Fabric:** Polyester/Nylon

**Top Surface:** Smooth Cover

**Top Cover Thickness:** 0.1875"

**Bottom Surface:** Smooth Cover

**Bottom Cover Thickness:** 0.0625"

**Compound:** SBR

**Work Tension:** 330 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.217 lbs./PIW

**Working Temp. (F):** -20 to 250

**Max. Stocked Width:** 96"

**Attributes:** Troughable

**Hardness:** 65a

**Minimum Pulley Chart:**

| Tension Rating          | Min. Pulley Dia. |
|-------------------------|------------------|
| Over 80%                | 18"              |
| 60%-80%                 | 16"              |
| 40%-60%                 | 14"              |
| Below 40%, tails, snubs | 12"              |

**Features:** 5-3731 features a smooth top and bottom surface. The heavy cover and high strength synthetic fabric results in a long wearing, mildew and rot resistant, low stretch belt. 330 3/16 x 1/16 STD is excellent for high abrasion applications. It is popular in the sand, gravel and rock industries as well as other heavy industrial applications.

