

Phone: 800-253-6300
Fax: 201-337-6540
mulhernbelting.com
sales@mulhernbelting.com

NOW STOCKING!

Part Number 5-3841

# 3-PLY 600 3/8" x 1/8"



Color: Black

Nominal OAG: 0.687" +/- .030

Plies: 3

Fabric: Polyester/Nylon

**Minimum Pulley Diameter: 24"** 

Top Surface: 3/8" SBR
Bottom Surface: 1/8" SBR

**Compound: SBR** 

Work Tension: 600 lbs. PIW Elongation: less than 4% Weight P.I.W. / Ft: 0.375

Working Temperature: -20F to 250F

Joining Method: R5/R6 Lacing

Mulhern Belting's **5-3841** features a 3-ply 600 lbs PIW carcass with a smooth top and bottom surface. The beefy 3/8" thick top cover and high strength synthetic fabric results in a long-wearing, mildew and rot resistant, low-stretch belt. 3-Ply 600  $3/8 \times 1/8$  is excellent for heavy duty, high weight, abrasive applications. It is used to convey gravel, rock, ore, limestone and many other industrial materials.

CALIFEROPA





- Service
- In-House Fabrication
- Multiple Stocking Locations
- On-Time Delivery
- Quality





### Lacing

The complete Flexco line of products: Standard Lacing; Recessed Lacing; Hidden Lacing; Cover Flap Lacing; Plastic Rivet Lacing; Plastic Spiral Lacing



#### **Endless**

Complete Thermoplastic and Rubber Vulcanization: Lap Splices; Finger Splices; Double Finger Splices; Skived Splices; Stitched Reinforcement; Prepared Ends



#### **Thermoplastic Profiles**

Tee Cleats; Beefy Cleats; Scoop Cleats; Thin Line Cleats; Fabric Reinforced Cleats; Curved Cleat Patterns; Chevron Cleat Patterns; V-Guides; Flanges; Lugs; Sidewall with and without a base



## Hot-Molded Rubber Profiles

Sidewall; Tee Cleats; SI Cleats; Scoop Cleats; Lugs; V-Guides; Flanges; Chevron Patterns; Bucket Patterns; Versa Patterns



#### **Specialty Fabrications**

Longitudinal Splicing; Covered Timing Belts and V-Belts; APC Belts; Capped Edges; Pulley Lagging; Loop Belts; Teflon Fiberglass Mesh Belts; Grooved and Beveled Belts; Splice Kits



**Hole Punching** 

Punching for Bucket Elevators or Perforations

**CONTACT US FOR A QUOTE TODAY!** WWW.MULHERNBELTING.COM



Phone: **1-800-253-6300** Fax: **1-201-337-6540** 

sales@mulhernbelting.com