

Phone: 800-253-6300 Fax: 201-337-6540 mulhernbelting.com sales@mulhernbelting.com

Part Number 5-4833

4 PLY 440 1/4" X 1/16" HIGH TEMP



Color: Black

Nominal OAG: 0.500" +/- .030

Plies: 4

Fabric: Polyester/Nylon

Minimum Pulley Diameter: 24"

Top Surface: 1/4"

Bottom Surface: 1/16"

Compound: EPDM

Work Tension: 440 lbs. PIW Elongation: less than 4% Weight P.I.W. / Ft: 0.270 lbs.

Working Temperature: -20F to 400F Joining Method: Lap Splice/Lacing

Mulhern Belting's 5-4833 features a wide temperature range with a high temperature up to 350F (fines) and 400F (lumps). When used in the recommended service range the compound resists hardening and cracking. It is also highly ozone resistant. You will find this belt in high weight, high temperature applications.







- Service
- In-House Fabrication
- Multiple Stocking Locations
- On-Time Delivery
- Quality





Lacing

The complete Flexco line of products: Standard Lacing; Recessed Lacing; Hidden Lacing; Cover Flap Lacing; Plastic Rivet Lacing; Plastic Spiral Lacing



Endless

Complete Thermoplastic and Rubber Vulcanization: Lap Splices; Finger Splices; Double Finger Splices; Skived Splices; Stitched Reinforcement; Prepared Ends



Thermoplastic Profiles

Tee Cleats; Beefy Cleats; Scoop Cleats; Thin Line Cleats; Fabric Reinforced Cleats; Curved Cleat Patterns; Chevron Cleat Patterns; V-Guides; Flanges; Lugs; Sidewall with and without a base



Hot-Molded Rubber Profiles

Sidewall; Tee Cleats; SI Cleats; Scoop Cleats; Lugs; V-Guides; Flanges; Chevron Patterns; Bucket Patterns; Versa Patterns



Specialty Fabrications

Longitudinal Splicing; Covered Timing Belts and V-Belts; APC Belts; Capped Edges; Pulley Lagging; Loop Belts; Teflon Fiberglass Mesh Belts; Grooved and Beveled Belts; Splice Kits



Hole Punching

Punching for Bucket Elevators or Perforations

CONTACT US FOR A QUOTE TODAY! WWW.MULHERNBELTING.COM



Phone: 1-800-253-6300 Fax: 1-201-337-6540

sales@mulhernbelting.com