

Phone: 800-253-6300
Fax: 201-337-6540
mulhernbelting.com
sales@mulhernbelting.com

Part Number 5-3635

3 PLY 600 1/16" X 1/16" M-MOR-SC



Color: Black

Nominal OAG: .360 +/- .030

Plies: 3

Fabric: Polyester/Nylon

Minimum Pulley Diameter: 24"

Top Surface: 1/16"
Bottom Surface: 1/16"
Compound: MSHA/MOR/SC
Work Tension: 600 lbs. PIW
Elongation: less than 4%
Weight P.I.W. / Ft: .193 lbs.

Working Temperature: 0F to 250F Joining Method: Lap Splice/Lacing

Mulhern Belting's 5-3635 is static conductive, moderately oil resistant, fire retardant and MSHA approved for grain elevators. It is excellent for bucket elevator applications and conveying oily grains and wood chips. Mulhern Belting can punch a wide variety of patterns for any bucket configuration.







- Service
- In-House Fabrication
- Multiple Stocking Locations
- On-Time Delivery
- Quality





Lacing

The complete Flexco line of products: Standard Lacing; Recessed Lacing; Hidden Lacing; Cover Flap Lacing; Plastic Rivet Lacing; Plastic Spiral Lacing



Endless

Complete Thermoplastic and Rubber Vulcanization: Lap Splices; Finger Splices; Double Finger Splices; Skived Splices; Stitched Reinforcement; Prepared Ends



Thermoplastic Profiles

Tee Cleats; Beefy Cleats; Scoop Cleats; Thin Line Cleats; Fabric Reinforced Cleats; Curved Cleat Patterns; Chevron Cleat Patterns; V-Guides; Flanges; Lugs; Sidewall with and without a base



Hot-Molded Rubber Profiles

Sidewall; Tee Cleats; SI Cleats; Scoop Cleats; Lugs; V-Guides; Flanges; Chevron Patterns; Bucket Patterns; Versa Patterns



Specialty Fabrications

Longitudinal Splicing; Covered Timing Belts and V-Belts; APC Belts; Capped Edges; Pulley Lagging; Loop Belts; Teflon Fiberglass Mesh Belts; Grooved and Beveled Belts; Splice Kits



Hole Punching

Punching for Bucket Elevators or Perforations

CONTACT US FOR A QUOTE TODAY! WWW.MULHERNBELTING.COM



Phone: 1-800-253-6300 Fax: 1-201-337-6540

sales@mulhernbelting.com