



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 1-2002: 2 Ply OHGR

**Color:** White

**Plies:** 2

**Nom. OAG:** 0.09" +/- 0.015"

**Fabric:** Polyester

**Top Surface:** 3/64" Smooth Cover

**Top Cover Thickness:** 0.046"

**Bottom Surface:** Friction Surface

**Compound:** NBR

**Work Tension:** 70 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.054 lbs./PIW

**Minimum Pulley:** 2"

**Backflex Min. Pulley Dia.:** 3"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 72"

**Attributes:** FDA Compliant, Oil Resistant,  
Sliderbed Suitable

**Top Cover Coefficient of Friction:** 1.4

**Bottom Cover Coefficient of Friction:** 0.3

**Features:** This belt features a special fabric treatment to ensure the highest ply adhesion possible and the lowest moisture saturation. 2 Ply OHGR is one of the most popular food belts available. It is used in most all FDA, USDA and agricultural applications due to its low moisture absorption and its high resistance to oil and grease. This belt is very popular in the meat and fish industry.

