



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

2-1120: B1200 FBS

Color: Black

Plies: 1

Nom. OAG: 0.11" +/- 0.02"

Fabric: Interwoven Polyester

Top Surface: Friction Surface

Bottom Surface: Friction Surface

Compound: PVC

Work Tension: 120 lbs./PIW

Elongation: Less than 2%

Weight: 0.054 lbs./PIW

Minimum Pulley: 2"

Backflex Min. Pulley Dia.: 3"

Working Temp. (F): 0 to 180

Max. Stocked Width: 72"

Attributes: Fire Retardant, Sliderbed Suitable

Top Cover Coefficient of Friction: 0.24

Bottom Cover Coefficient of Friction: 0.23

Features: This belt features the popular interwoven carcass. It offers high strength, tear resistance, low stretch and high lace retention. B1200 FBS is a medium duty general purpose conveyor belt that can be used in most industries. This is a very popular belt for trash conveyors. We also include this belt in our food line as it is an excellent depanner belt. This belt is fire resistant.






Splicing Instructions



Part Number: 2-1120

Part Description: B1200 FBS



	Imperial	Metric
Finger Length (A):	3"	76 mm
Finger Width (B):	3/4"	19 mm

	Water Cooled		Hi-Speed	
	Imperial	Metric	Imperial	Metric
Upper Platen Temp:	340 ° F	171 ° C	340 ° F	171 ° C
Bottom Platen Temp:	340 ° F	171 ° C	340 ° F	171 ° C
Pressure:	50 PSI	3.4 bar	36 PSI	2.5 bar
Time:	01:00 m:s	01:00 m:s	03:00 m:s	03:00 m:s

Press Layout	Description	Part # to Order
	Top Heating Platen with equalizing plate	
	Teflon	6-3000
	Meltable Foil (optional)	8341C
	Belt	2-1120
	Teflon	6-3000
	Bottom Heating Platen with equalizing plate	

For high stress applications splice with reinforcing fabric.