



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

3-1213: 3 Ply MOR Rough Top

Color: Black

Plies: 3

Nom. OAG: 0.3" +/- 0.03"

Recessed OAG: 0.13"

Fabric: Cotton/Polyester

Top Surface: Hemp Impression Rough Top

Bottom Surface: Bare Surface

Compound: MOR

Work Tension: 225 lbs./PIW

Elongation: Less than 2%

Weight: 0.12 lbs./PIW

Minimum Pulley: 3"

Backflex Min. Pulley Dia.: 4.5"

Working Temp. (F): -20 to 250

Max. Stocked Width: 72"

Attributes: Sliderbed Suitable, Troughable, Oil Resistant

Top Cover Coefficient of Friction: 1

Bottom Cover Coefficient of Friction: 0.3

Features: 3-1213 offers excellent gripping for standard incline conveyors. The MOR compound ensures oil resistant. The Cotton/Polyester carcass gives a hefty appearance and a cushioning effect on the conveyed product. NOTE--The Rough Top must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. 3 Ply MOR Rough Top will handle most all products including boxed, bagged or packaged goods. The MOR is oil resistant.

