



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 3-1313: 3 Ply Blue R/T

**Color:** Blue

**Plies:** 3

**Nom. OAG:** 0.313" +/- 0.02"

**Recessed OAG:** 0.16"

**Fabric:** Polyester

**Top Surface:** Hemp Impression Rough Top

**Bottom Surface:** Skim

**Compound:** XNBR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.12 lbs./PIW

**Minimum Pulley:** 2.5"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 72"

**Attributes:** Abrasion Resistant

**Top Cover Coefficient of Friction:** 1.2

**Bottom Cover Coefficient of Friction:** 0.3

**Features:** The Carboxylated Nitrile Compound has been proven to out perform even Urethane in wear resistance and at the same time have oil resistance. The belt will normally out last SBR or neoprene roughtops. NOTE: The roughtop profile must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. 3 Ply Blue Roughtop is particularly popular in the paper and cardboard box industries. It is also popular in any application where any high abrasive or oily conditions exist.

