



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 3-1313Z: Blue Rough Top Ziplink

**Color:** Blue

**Plies:** 1

**Nom. OAG:** 0.29" +/- 0.03"

**Fabric:** Plastic Mesh

**Top Surface:** Hemp Impression Rough Top

**Bottom Surface:** Bare

**Compound:** XNBR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 1%

**Weight:** 0.09 lbs./PIW

**Minimum Pulley:** 3"

**Backflex Min. Pulley Dia.:** 4.5"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 72"

**Attributes:** Abrasion Resistant, Sliderbed Suitable

**Top Cover Coefficient of Friction:** 0.9

**Bottom Cover Coefficient of Friction:** 0.1

**Features:** 3-1313Z features a ziplink splice to solve problems in applications where lace retention or installing an endless belt is a problem. The Carboxylated NBR compound is abrasion resistant. Blue Rough Top Ziplink is a problem solving belt for light and medium industrial applications. The Ziplink splice is smooth and non-metallic and combines the convenience of a laced belt with the splice tension rating of an endless belt. This belt is popular in the cardboard box industry.

