



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 3-4102: 2 Ply Black Diamond Top

**Color:** Black

**Plies:** 2

**Nom. OAG:** 0.33" +/- 0.02"

**Recessed OAG:** 0.15"

**Fabric:** Polyester

**Top Surface:** Diamond Top Impression

**Bottom Surface:** Bare

**Compound:** SBR

**Work Tension:** 120 lbs./PIW

**Elongation:** Less than 3%

**Weight:** 0.093 lbs./PIW

**Minimum Pulley:** 2.5"

**Backflex Min. Pulley Dia.:** 3.75"

**Working Temp. (F):** -20 to 250

**Max. Stocked Width:** 72"

**Attributes:** Sliderbed Suitable

**Hardness:** 45a

**Top Cover Coefficient of Friction:** 1.9

**Bottom Cover Coefficient of Friction:** 0.3

**Features:** 3-4102 is used for the steepest inclines where high performance is needed. The belt offers an unusually high coefficient of friction. NOTE--The rough top impression must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. 2 Ply Black Diamond Top is used in boxed, bagged and packaged goods applications. It is also popular in the airline industry and in post offices.

