



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 3-4402: 2 Ply Tan Diamond Top

**Color:** Tan

**Plies:** 2

**Nom. OAG:** 0.313" +/- 0.02"

**Recessed OAG:** 0.15"

**Fabric:** Polyester

**Top Surface:** Diamond Top Impression

**Bottom Surface:** Bare

**Compound:** SBR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.093 lbs./PIW

**Minimum Pulley:** 2.5"

**Backflex Min. Pulley Dia.:** 3.75"

**Working Temp. (F):** -25 to 250

**Max. Stocked Width:** 72"

**Attributes:** Sliderbed Suitable, Non-Marking

**Hardness:** 45a

**Top Cover Coefficient of Friction:** 1.9

**Bottom Cover Coefficient of Friction:** 0.3

**Features:** 3-4402 is normally used for the steepest inclines where high performance is needed. This belt has an unusually high coefficient of friction. NOTE--the rough top impression must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. 2 Ply Tan Diamond Top is used for boxed, bagged and packaged goods applications. This belt is also popular in the airline industry and in the post office. This belt is also non-marking.

