



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 3-7102: 2 Ply Steep Grade

**Color:** Black

**Plies:** 2

**Nom. OAG:** 0.287" +/- 0.02"

**Recessed OAG:** 0.13"

**Fabric:** Polyester

**Top Surface:** Oval Shaped Nubs

**Bottom Surface:** Bare

**Compound:** SBR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 2%

**Weight:** 0.1 lbs./PIW

**Minimum Pulley:** 2"

**Backflex Min. Pulley Dia.:** 3"

**Working Temp. (F):** -25 to 250

**Max. Stocked Width:** 60"

**Attributes:** Sliderbed Suitable

**Top Cover Coefficient of Friction:** 0.8

**Bottom Cover Coefficient of Friction:** 0.2

**Features:** This belt offers excellent gripping for the highest inclines (up to 45 degrees for some products). This is an old time favorite for many industrial applications. NOTE--The rough top impression must be recessed to use lacing. Use Recessed OAG for Lacing Recommendation. 2 Ply Steep Grade is used for some of the steepest inclines. The belt also prevents breakage due to the cushion effect of it's profile. It is very popular in the airline industry and bottling plants.

