



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 4-1314Z: Blue Smooth Top Zip-Link x Bare

**Color:** Blue

**Plies:** 1

**Nom. OAG:** 0.134" +/- 0.015"

**Fabric:** Plastic Mesh

**Top Surface:** 1/32" Top Cover

**Bottom Surface:** Bare

**Compound:** XNBR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 1%

**Weight:** 0.06 lbs./PIW

**Minimum Pulley:** 2"

**Backflex Min. Pulley Dia.:** 3.5"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 72"

**Attributes:** Sliderbed Suitable

**Top Cover Coefficient of Friction:** 0.8

**Bottom Cover Coefficient of Friction:** 0.35

**Features:** The ziplink splice on this belt solves problems in applications where lace retention is a problem. The Carboxylated NBR carcass is extremely abrasion resistant. Blue Smooth Top Ziplink is a problem solving belt for light to medium industrial applications. The Ziplink splice combines the convenience of a laced belt with the splice tension rating of an endless belt and a smooth non-metallic splice. This belt is popular in canning operations and cardboard box plants.

