



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 5-1511: 2 Ply 150 1/8 x 1/32 STD

**Color:** Black

**Plies:** 2

**Nom. OAG:** 0.236" +/- 0.03"

**Fabric:** Polyester

**Top Surface:** Smooth Cover

**Top Cover Thickness:** 0.125"

**Bottom Surface:** Smooth Cover

**Bottom Cover Thickness:** 0.0312"

**Compound:** SBR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 3%

**Weight:** 0.137 lbs./PIW

**Working Temp. (F):** -20 to 200

**Max. Stocked Width:** 84"

**Attributes:** Troughable

**Hardness:** 65a

**Minimum Pulley Chart:**

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

**Features:** 5-1511 features a smooth top and bottom surface. The heavier cover with the high strength synthetic fabric results in a long wearing, mildew and rot resistant, low stretch belt. 150 1/8" x 1/32" STD is excellent for moderately abrasive applications. It is popular in the sand, gravel and lumber industries.

