



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-3635: 3 Ply 600 1/16 x 1/16 M-MOR-SC

Color: Black

Plies: 3

Nom. OAG: 0.36" +/- 0.03"

Fabric: Polyester/Nylon

Top Surface: Smooth Cover

Top Cover Thickness: 0.0625"

Bottom Surface: Smooth Cover

Bottom Cover Thickness: 0.0625"

Compound: SCORF

Work Tension: 600 lbs./PIW

Elongation: Less than 4%

Weight: 0.193 lbs./PIW

Minimum Pulley: 18"

Working Temp. (F): 0 to 250

Max. Stocked Width: 60"

Attributes: Troughable, Static Conductive to $< 3 \times 10^8$ ohms, OSHA 29 CFR, Oil Resistant, Fire Retardant

Hardness: 65a

Minimum Pulley Chart:

Tension Rating	Min. Pulley Dia.
Over 80%	30"
60%-80%	24"
40%-60%	20"
Below 40%, tails, snubs	18"

Features: Mulhern Belting's 5-3635 is static conductive, moderately oil resistant, fire retardant and MSHA approved for grain elevators. It is excellent for bucket elevator applications and conveying oily grains and wood chips. Mulhern Belting can punch a wide variety of patterns for any bucket configuration.

