



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 5-3831: 3 Ply 330 1/4 x 1/16 STD

**Color:** Black

**Plies:** 3

**Nom. OAG:** 0.48" +/- 0.03"

**Fabric:** Polyester/Nylon

**Top Surface:** Smooth Cover

**Top Cover Thickness:** 0.25"

**Bottom Surface:** Smooth Cover

**Bottom Cover Thickness:** 0.0625"

**Compound:** SBR

**Work Tension:** 330 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.26 lbs./PIW

**Working Temp. (F):** -20 to 250

**Max. Stocked Width:** 96"

**Attributes:** Troughable

**Hardness:** 65a

**Minimum Pulley Chart:**

Tension Rating	Min. Pulley Dia.
Over 80%	18"
60%-80%	16"
40%-60%	14"
Below 40%, tails, snubs	12"

**Features:** 5-3831 features a smooth top and bottom surface. The heavy cover and high strength synthetic fabric results in a long wearing, mildew and rot resistant, low stretch belt. 330 1/4 x 1/16 STD is excellent for heavy duty abrasive applications. It is used to convey gravel, rock, ore, limestone and many other industrial materials. It is also used as an elevator belt.

