



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 5-3833: 330 1/4 x 1/16 HT

**Color:** Black

**Plies:** 3

**Nom. OAG:** 0.48" +/- 0.03"

**Fabric:** Polyester/Nylon

**Top Surface:** Smooth Cover

**Top Cover Thickness:** 0.25"

**Bottom Surface:** Smooth Cover

**Bottom Cover Thickness:** 0.0625"

**Compound:** EPDM

**Work Tension:** 330 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.26 lbs./PIW

**Working Temp. (F):** -20 to 400

**Max. Stocked Width:** 72"

**Attributes:** Heat Resistant, Troughable

**Hardness:** 65a

**Minimum Pulley Chart:**

| Tension Rating          | Min. Pulley Dia. |
|-------------------------|------------------|
| Over 80%                | 18"              |
| 60%-80%                 | 16"              |
| 40%-60%                 | 14"              |
| Below 40%, tails, snubs | 12"              |

**Features:** 5-3833 features a wide temperature range, with a high temperature up to 350F (fines) and 400F (lumps). When used in its recommended service range it resists hardening and cracking. It is also highly ozone resistant. 330 1/4 x 1/16 HT is used in many high heat, high abrasion applications--- such as a foundry.

