



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-3841: 3 Ply 600 3/8 x 1/8 STD

Color: Black

Plies: 3

Nom. OAG: 0.687" +/- 0.03"

Fabric: Polyester/Nylon

Top Surface: Smooth Cover

Top Cover Thickness: 0.375"

Bottom Surface: Smooth Cover

Bottom Cover Thickness: 0.125"

Compound: SBR

Work Tension: 600 lbs./PIW

Elongation: Less than 4%

Weight: 0.375 lbs./PIW

Working Temp. (F): -20 to 250

Max. Stocked Width: 72"

Attributes: Troughable

Hardness: 65a

Minimum Pulley Chart:

Tension Rating	Min. Pulley Dia.
Over 80%	30"
60%-80%	24"
40%-60%	20"
Below 40%, tails, snubs	18"

Features: 5-3841 features a 3 ply 600 lbs. PIW carcass and a smooth top and bottom surface. The beefy 3/8" thick top cover and high strength synthetic fabric results in a long wearing, mildew and rot resistant, low stretch belt. 3 Ply 600 3/8 x 1/8 STD is excellent for heavy duty, high weight, abrasive applications. It is used to convey gravel, rock, ore, limestone and many other industrial materials. It is also used as an elevator belt.

