



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 5-7532: 2 Ply 220 1/8 x 3/32 Cleated Incline - MOR

**Color:** Black

**Plies:** 2

**Nom. OAG:** 0.57" +/- 0.03"

**Recessed OAG:** 0.325"

**Fabric:** Polyester

**Top Surface:** 1/4" Chevron Profile

**Top Cover Thickness:** 0.125"

**Bottom Surface:** Smooth Cover

**Bottom Cover Thickness:** 0.0937"

**Compound:** MOR

**Work Tension:** 220 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.214 lbs./PIW

**Working Temp. (F):** -20 to 225

**Max. Stocked Width:** 72"

**Attributes:** Troughable, Oil Resistant

**Hardness:** 65a

**Minimum Pulley Chart:**

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

**Features:** 5-7532 features a 1/4" high, 6" wide chevrons profile in a staggered pattern. The compound is MOR. The OAG includes the profile. Use Recessed OAG for Lacing Recommendation. 220 1/8 x 3/32 Cleated Incline MOR is popular carrying bulk grain as well as gravel and crushed stone. It is used on road planners.

