



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 5-8502: 3 Ply 330 1/8 x Bare Cleated Incline - MOR

**Color:** Black

**Plies:** 3

**Nom. OAG:** 0.57" +/- 0.03"

**Recessed OAG:** 0.335"

**Fabric:** Polyester/Nylon

**Top Surface:** 1/4" Chevron Profile

**Top Cover Thickness:** 0.125"

**Bottom Surface:** Bare

**Compound:** MOR

**Work Tension:** 330 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.201 lbs./PIW

**Working Temp. (F):** -20 to 225

**Max. Stocked Width:** 72"

**Attributes:** Sliderbed Suitable, Troughable, Oil Resistant

**Hardness:** 65a

**Minimum Pulley Chart:**

Tension Rating	Min. Pulley Dia.
Over 80%	18"
60%-80%	16"
40%-60%	14"
Below 40%, tails, snubs	12"

**Features:** 5-8502 features a 1/4" high, 6" wide chevron profile in a staggered pattern. The OAG includes the profile. Use the Recessed OAG for the Lacing Recommendation. 3 Ply 1/8" x Bare Cleated Incline MOR is popular in bulk conveying where oil is a concern. This is a popular specification on Diamond Z grinders.

