



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 5-8531: 3 Ply 330 1/8 x 1/16 Cleated Incline - SBR

**Color:** Black

**Plies:** 3

**Nom. OAG:** 0.595" +/- 0.04"

**Recessed OAG:** 0.35"

**Fabric:** Polyester/Nylon

**Top Surface:** 1/4" Chevron Profile

**Top Cover Thickness:** 0.125"

**Bottom Surface:** Smooth Cover

**Bottom Cover Thickness:** 0.0625"

**Compound:** SBR

**Work Tension:** 330 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.225 lbs./PIW

**Working Temp. (F):** -25 to 250

**Max. Stocked Width:** 84"

**Attributes:** Troughable

**Hardness:** 65a

**Minimum Pulley Chart:**

Tension Rating	Min. Pulley Dia.
Over 80%	18"
60%-80%	16"
40%-60%	14"
Below 40%, tails, snubs	12"

**Features:** 5-8531 features 1/4" high, 6" wide chevron profiles in a staggered pattern. The OAG includes the profile. Use Recessed OAG for Lacing Recommendation. 330 1/8 x 1/16 Cleated Incline SBR is a popular bulk conveying belt.

