



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 5-8642: 2 Ply 150 Mini-Bite 1/32" x Bare

**Color:** Black

**Plies:** 2

**Nom. OAG:** 0.29" +/- 0.03"

**Fabric:** Polyester

**Top Surface:** Mini-Bucket Profile

**Top Cover Thickness:** 0.0312"

**Bottom Surface:** Bare

**Compound:** SBR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.085 lbs./PIW

**Minimum Pulley:** 8"

**Working Temp. (F):** -25 to 250

**Max. Stocked Width:** 72"

**Attributes:** Troughable

**Hardness:** 65a

**Minimum Pulley Chart:**

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

**Features:** 5-8642 features a 3/16" high by 1-3/4" wide bucket profile in a staggered pattern. The cleats are spaced on 2" centers across the belt and 1" centers down the length. The OAG of the belt includes the profile. 2 Ply 150 Mini-Bite 1/32" x Bare is popular for carrying gravel, dirt and sands. It is also used in the recycling industry.

